

2017-06-26
Blue Systems AB
info@bluesystems.se | +46 (0)31-29 72 16

Title:
DoP L2-v.I

Declaration of Performance according to CPR Annex III No. L2-v.I

Product code

SAFENCE 3RC-17 & 4RC-17

Use

Two-sided guardrail to be installed as median barrier and/or side barrier of busy road.

Manufacturer

Blue Systems AB, Fiskebäcks Hamn 16, SE-426 58 Västra Frölunda.

Assessment and verification of constancy of performance

AVCP system 1: 0402-CPR-SC0560-11

Harmonised standard

EN 1317-5:2007 +A2:2012/AC:2013

Notified body

RISE Research Institutes of Sweden (ID: 0402)


Declared performance

Essential characteristics	Performance	Harmonised technical specification
3,0 m post distance	Containment level: L2 including H2 Impact severity: A Normalised working width: W_{N8} (3,2 m) Normalised dynamic deflection: 3,2 m Norm. vehicle intrusion: V_{N8} 3,3 m Resistance to snow removal: Class 2	EN 1317-5:2007 +A2:2012/AC:2013

Attestation

The performance of the product identified in this document is in conformity with declared performance. This declaration of performance is issued in accordance with regulation (EU) no. 305/2011 under the sole responsibility of the manufacturer identified in this document.

Signed for and on behalf of the manufacturer by



Håkan Nilsson, CEO - Blue Systems AB
Gothenburg, 2017-06-26