

2016-06-28 Blue Systems AB info@bluesystems.se | +46 (0)31-29 72 16 Title: DoP N2-v.III

Declaration of Performance according to CPR Annex III No. N2-v.III

Product code

SAFENCE 3RC-96, 3RI-96, 4RC-96 & 4RI-96

Use

Two-sided cable barrier to be installed as median barrier and/or side barrier of busy road.

Manufacturer

Blue Systems AB, Fiskebäcks Hamn 16, SE-426 58 Västra Frölunda

Assessment and verification of constancy of performance

AVCP system 1: 0402-CPR-SC0560-11

Harmonised standard

EN 1317-5:2007 +A2:2012/AC:2013

Notified body

SP Sveriges Tekniska Forskningsinstitut (ID: 0402)

Declared performance

Essential characteristics	Performance	Harmonised technical specification
2,5 m post distance	Containment level: N2	EN 1317-5:2007 +A2:2012/AC:2013
	Impact severity: A	
	Normalized working width: W_N4 (1,3 m)	
	Normalized dynamic deflection: 1,3 m	
	Resistance to snow removal: Class 2	
3,0 m post distance	Containment level: N2	EN 1317-5:2007 +A2:2012/AC:2013
	Impact severity: A	
	Normalized working width: $W_N = (1,6 \text{ m})$	
	Normalized dynamic deflection: 1,6 m	
	Resistance to snow removal: Class 2	

Attestation

The performance of the product identified in this document is in conformity with declared performance. This declaration of performance is issued in accordance with regulation (EU) no. 305/2011 under the sole responsibility of the manufacturer identified in this document.

Tel: +46 (0)31-29 72 16

Fax: +46 (0)31-29 30 65

E-mail: info@bluesystems.se

Internet: www.bluesystems.se

Signed for and on behalf of the manufacturer by

Håkan Nilsson, CEO - Blue Systems AB

Gothenburg, 2016-06-28