

2016-06-28
Blue Systems AB
info@bluesystems.se | +46 (0)31-29 72 16

Title:
DoP H2-v.I

Declaration of Performance according to CPR Annex III No. H2-v.I

Product code

SAFENCE 4RC-08 & 4RI-08

Use

Two-sided cable barrier to be installed as median barrier and/or side barrier of busy road.

Manufacturer

Blue Systems AB, Fiskebäcks Hamn 16, SE-426 58 Västra Frölunda.

Assessment and verification of constancy of performance

AVCP system 1: 0402-CPR-SC0560-11

Harmonised standard

EN 1317-5:2007 +A2:2012/AC:2013

Notified body

SP Sveriges Tekniska Forskningsinstitut (ID: 0402)


Declared performance

Essential characteristics	Performance	Harmonised technical specification
1,5 m post distance	Containment level: H2 Impact severity: A Normalised working width: W_N8 (2,7 m) Normalised dynamic deflection: 2,5 m Norm. vehicle intrusion: V_N8 (3,3 m) Resistance to snow removal: Class 2	EN 1317-5:2007 +A2:2012/AC:2013

Attestation

The performance of the product identified in this document is in conformity with declared performance. This declaration of performance is issued in accordance with regulation (EU) no. 305/2011 under the sole responsibility of the manufacturer identified in this document.

Signed for and on behalf of the manufacturer by



Håkan Nilsson, CEO - Blue Systems AB
Gothenburg, 2016-06-28