

## DECLARATION of PERFORMANCE (DoP)

*No. SafeLine-R (N2) – T521-1*

Manufacturer	Vik Ørsta AS Box 193, N-6151 Ørsta, Norway Telephone: +47 70 04 70 00	Web: www.Vikorsta.no
Product identification code	SafeLine-R – safety barrier c/c 4 m and c/c 6 m	
Product type	SafeLine-R N2-W3-CC4 and SafeLine-R N2-W4-CC6	
Intended use	In vehicle circulation areas / roads	
Harmonized standard	EN 1317-5:2007 / A2:2012	
System of assessment and verification	System 1 (CPR no. 305/2011)	
Name of notified body	RISE Research Institute of Sweden	
Identification number of the notified body	No. 0402	
Description of the notified body tasks	Performed the initial type-testing for the relevant characteristics of the product, the initial inspection of the factory and of the factory production control and performs the continuous surveillance, assessment and approval of the factory production control	
EC Certificate of Conformity	No. 0402 – CPR - SC0212-19	

Declared performance		
Essential characteristics	Performance	Harmonized standard
Performance under impact:	c/c 4m      c/c 6m	
- containment level	N2              N2	EN 1317-5:2007 / A2:2012
- impact severity	A                A	EN 1317-5:2007 / A2:2012
- working width	1,0 m (W3)    1,3 m (W4)	EN 1317-5:2007 / A2:2012
- dynamic deflection	0,9 m          1,1 m	EN 1317-5:2007 / A2:2012
- vehicle intrusion	Not applicable    Not applicable	
Resistance to snow removal:	Class 4	EN 1317-5:2007 / A2:2012
Durability:		
- of performance under impact	Hot dip galvanized coatings according to NS-EN ISO 1461 and Statens Vegvesen handbook N101	EN 1317-5:2007 / A2:2012
- of resistance to snow removal		EN 1317-5:2007 / A2:2012

The performance of the product is in conformity with the declared performance. This declaration of performance is issued under the sole responsibility of the manufacturer.

Signed for and on behalf of  
the manufacturer by:

*John H. Systad*  
-Product manager-



Vik i Sogn    2019-11-29